

## ROTARY UNIT SPECIFICATION

	<b>3-TIER</b>	<b>4-TIER</b>	<b>5-TIER</b>	<b>6-TIER</b>	<b>7-TIER</b>	<b>8-TIER</b>
CAT. NO - Starter	231SE-GM	241SE-GM	251SE-GM	261SE-GM	271SE-GM	281SE-GM
Add-On	231AE-GM	241AE-GM	251AE-GM	261AE-GM	271AE-GM	281AE-GM
HEIGHT	41.6" 1057mm	48.6" 1235mm	60.875" 1546mm	71.375" 1813mm	82.00" 2083mm	92.50" 2350mm
WIDTH - Starter	45.25"/1149mm 38.125"/968mm					
Add-On						
DEPTH (Plus 7"/180mm when placed against a wall)	31.00"/787mm					
NO. OF LEVELS	6	8	10	12	14	16
FILING CAPACITY PER UNIT	4572mm	6096mm	7620mm	9144mm	10668mm	12192mm
WEIGHT STARTER – Empty	127kgs	155kgs	175kgs	200kgs	225kgs	243kgs
Laden	298kgs	381kgs	463kgs	540kgs	622kgs	697kgs
WEIGHT ADD ON – Empty	108kgs	125kgs	149kgs	165kgs	184kgs	200kgs
Laden	279kgs	352kgs	432kgs	505kgs	581kgs	654kgs
FLOOR SPACE OCCUPIED – Starter	1.11m <sup>2</sup> 0.94m <sup>2</sup>					
Add-On						
COLOUR	Grey Mist					

- 1) No. of levels and capacity figures are based on standard shelf filing using foolscap folders stored on their long edge.
- 2) All internal fitments are fully adjustable as vernier are spaced at 1.75".
- 3) Each unit is fitted with a cylinder lock and one foot pedal. The bottom shelf is fixed.